

Uncompromising performance. Bold design.

Raising the bar in guest room telephone performance and design.

Introducing Marquis® 3300 Series telephones by TeleMatrix. A bold new merger of design and engineering.

Feature

- Redial & Flash keys
- TouchLite® one-touch voice mail retrieval lightbar technology (Message waiting light only on 3300MWB, No message light on 3300LBY)
- ▶ 10, 5 or No programmable guest service keys
- Passthrough High Speed Internet Access port (standard)
- ▶ 5 Year "no hassle" warranty

Colours

- Light Ash
- Black
- Seven Standard Inserts (red, ochre, blue, gray, white, orange & lime)

Models

Single line non-speakerphones

- 3300LBY Lobby phone
- ► 3300MWB Basic phone
- ▶ 3300MW5 5 memory keys
- ▶ 3300MW10 10 memory keys



TELEMATRIX USA World Headquaters +1 719 638 8821 tel. +1 719 638 8815 fax.

TELEMATRIX EUROPE +44 (0) 1908 682180 tel. +44 (0) 1908 682189 fax.

TELEMATRIX MIDDLE EAST +971 4 2676550 tel. +971 4 2677361 fax.

TELEMATRIX INDIA PVT. LTD. +91 98 207 207 49 tel.

SCITEC & TELEMATRIX (Beijing) CO. LTD. +86 10 85911289 tel. +86 10 85911525 fax.

Questions: Info@telematrix.net Service: prioritycare@telematrix.net Web Site: www.telematrix.net

3300 Series Speakerphone Features & Specifications:

cifications:

Product Identification & Order Numbers: Single Line Non-Speakerphone:

- Model No. 3300LBY: Lobby phone
 P/N 33009 (light ash) / P/N 330091 (black)
- Model No. 3300MWB: Basic phone
 P/N 33039 (light ash) / P/N 330391 (black)
- Model No. 3305MW5: 5 Memory Keys
 P/N 33139 (light ash) / P/N 331391 (black)
- Model No. 3300MWD: 10 Memory Keys
 P/N 33239 (light ash) / P/N 332391 (black)
- Custom Colours available in minimum quantities of 250 or more for 'standard' coloured inserts and 500 or more for 'premium' colours.

Product Information:

- Installation Includes
 RJ25 Line Cord 15ft./4.5m
 Handset Coil Cord 9ft/2.25m
 Optional Wall Mount Bracket (Not included)
- Line, MW, and Ringer Specifications
 Line Voltage 24-52VDC (+/-)
 Line Current 20mA-100mA
 Switchable for 90VDC Neon or Low Voltage LED
 Reverse polarity switch (available on European Models)
 Ringer Equivalence 0.6B
- ► Unit Dimensions
- 8.5"/12.25cm(l) 6.75"/16.87cm(w) 3.5"/8.75cm(h)
- Packaging Weight MasterPack Quantities of 10 Units, 27lbs/13.2kg
- Certifications

FCC Part 68, FCC Part 15 & UL 1459 Ref. CE & ETL ADA/FCC Hearing Aid Compliant RoHS Environmentally Compliant



5025 Galley Road Colorado Springs, CO 80915 USA 1.800.462.9446 free N.America 719.638.8821 tel. 719.638.8815 fax. www.telematrix.net

Standard Features:

- Single Line Non-Speakerphone
- Compatible with PABX Systems
- Soft Key Technology
- Passthrough High Speed Access Port (standard)
- SteelTrap® Memory Technology no batteries required
- On-Hook Pre-Dialing on Memory Keys
- ► morePhone[™] Automatic Overshipment for Qualified Orders Over 100 Phones
- Turnkey Telephone Modifications Available Ready for Instant Installation
- ▶ Full Length Custom Tailored Faceplates
- Industrial Grade Construction with Matte Finish Design
- Non-Slip Base

Audio/Visual Features:

- Large, Bright Red, TouchLite® 1-Touch Message Waiting Retrieval Lamp (Message lamp only on 3300MWB, no lamp on 3300LBY
- ▶ 8 Step Speaker and Handset Volume Control
- ▶ High/Low Ringer Volume Switch

Programming Features:

- One-Touch, TouchLite® Message Retrieval (programmable)
- 10, 5 or No Guest Service Keys with Secure Programming
- Memory Key Entry Maximum 32 Digits
- Flash Key (submerged) 100 1000mS (programmable),
 600mS Timing (default), Storable
- Pause Key (submerged) 1.0 5.0 Sec. (programmable), Storable
- Store Key (submerged)



Seven Standard Custom Coloured Inserts All seven colours are good for black or ash telephones.* Minimum quantities do apply.

© TeleMatrix Inc., 2009. Product specifications and descriptions in this document subject to change without notice. TeleMatrix(®, TouchLite(®, SteelTrap(®) are registered trademarks. iPriorityCareSM, PriorityCareSM and morePhoneSM are service marks of TeleMatrix Inc. U.S. Patent No. 6556663, D448011.

MARQUIS SERIES

3300 SERIES Single Line Non-Speakerph<u>ones</u>